

No-Seize

Anti-Seize Compound



TECHNICAL DATA SHEET



Pre-treat metal parts to avoid seizing and breaking during removal.

No-Seize is a super high performance lubricant and sealant that protects against seizing, galling, rusting, torque, friction, corrosion and high temperatures.

- *Prevents galling (heat "binding"), seizing, pitting, thread distortion and galvanic action.*
- *Is non-melting and will not wash off.*
- *Protects against rust, corrosion, freezing and any other outdoor weather conditions.*
- *Will not evaporate, harden, separate or crack and will not fuse to metal.*
- *Protects stainless steel from pitting and gives aluminum high heat resistance.*
- *Chemical and solvent resistant.*
- *Protects metal parts under sustained temperatures up to 2,000°F (1,150°C).*



Great for any threaded fastener that will eventually require changing, such as:

Boiler Plates	Engines
Water & Gas Meters	Plows
Machinery Parts	Trucks

Use on:

Nuts	Pipe Threads
Bolts	Roller Pins
Screws	Hose Connections



EXTREME TEMPERATURE
(-20°F up to +2000°F)

**Extreme Pressure
Dry Lubricant and Sealant**

**PREVENTS GALLING, SEIZING AND
GALVANIC ACTION
PROTECTS AGAINST RUST AND CORROSION
WILL NOT WASH OFF
NET WT. 13 OZ. (369 g)**

**DANGER: FLAMMABLE
KEEP OUT OF REACH OF CHILDREN
CONTENTS UNDER PRESSURE
See Cautions on Back Panel**



SOLD BY
CONTINENTAL RESEARCH CORPORATION
PO Box 15204, St. Louis, MO 63110-0204
24 Hour Customer Hotline: **1-800-325-4869**
24 Hour Fax: (314) 776-6810
www.crcorp.com

**Contains No Chlorinated Solvents
(No 1,1,1-Trichloroethane)**

Prevents galling, seizing, pitting, fretting, corrosion and distortion of all threaded, keyed, splined and press fitted assemblies. Protects at sustained temperatures of up to +2000°F. Highly resistant to moisture, weather, chemical fumes, salt spray and steam. Allows tighter, more vibration-proof seals using less torque while making disassembly easier.

USE ON: Industrial machinery, construction, farm, mining and earth moving equipment, marine hardware, vehicle fleets and assembly lines.

DIRECTIONS: Preclean surfaces to be treated, removing any old contaminated grease, dirt or grit. Shake can thoroughly. With can held in upright position, spray surface in short bursts from a distance of 8 to 10 inches. After use, invert can and clear actuator by spraying until only gas is dispelled.

DANGER: Flammable. Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting.

CONTAINS (CAS#): Naphthenic Distillate (64742-53-6), Heptane (142-82-5), Propane/n-Butane (68476-86-8), Aluminum (7429-90-5),

KEEP OUT OF REACH OF CHILDREN

FIRST AID:

EXCESSIVE INHALATION: Remove to fresh air and call a physician.

IF EYE CONTACT: Flush with water for 15 minutes, lifting upper and lower lids. Get medical attention.

IF SWALLOWED: Do not induce vomiting, get medical attention immediately.

IF SKIN CONTACT: Wash affected area immediately with soap and water. If irritation persists, get medical attention.

HMIS RATING: Health, 1; Flammability, 3; Reactivity, 1; Personal Protection, B.



**Continental
Research
Corporation**