

Steel Deck

Stainless Steel Coating in a Can



TECHNICAL DATA SHEET



Resists Chemicals, Weather, Abrasion and Corrosion.

Steel Deck is a super-tough coating that contains 100% pure 316L stainless steel pigment in an ultra-durable acrylic lacquer resin base. One simple application of Steel Deck protects metal, wood, ceramics and leather from deterioration caused by harsh chemicals, severe weather or abrasion. Steel Deck will not turn dark or oxidize. Instead, it brightens with age.



**When worn,
old steel oxidizes**

**Steel Deck provides
superior protection**



- *Beautifies and protects*
- *Chemical and abrasion resistant*
- *Heat-resistant up to 400 °F*
- *Provides unmatched rust protection*
- *Use indoors or outdoors*
- *Satin sheen finish*
- *Tack-free in 5 minutes;
hard cure in 2 hours*

Ideal for use on:

- Radiators & Exhaust Fans
- Steam Pipes
- Boilers
- Heat Exchangers
- Engines
- Exhausts & Mufflers
- Fire Hydrants
- Parking Meters
- Chain & Wire Fences
- Lockers
- Flush Valves
- Refrigeration & Freezer Racks
- Hoods & Vents
- Storage & Mixing Tanks
- Marine Equipment
- Chemical Processing Equipment
- Washroom Partitions
- Agricultural Equipment
- Military Equipment
- Road Equipment
- Ovens
- Restaurant Equipment
- Dairy Equipment
- Stainless Steel Prep Tables
- Playground Equipment
- Bumpers, Mirrors, Tool Boxes



**Continental
Research
Corporation**

HASSLE FREE BUSINESS SINCE 1967

© 2010 Continental Research Corporation. [071610]



**LONG LASTING
SUPER TOUGH
ACRYLIC LACQUER
PROTECTS AGAINST:
RUST, CORROSION AND
CHEMICAL DAMAGE**

DANGER
FLAMMABLE LIQUID AND VAPOR
HARMFUL OR FATAL IF SWALLOWED
KEEP OUT OF REACH OF CHILDREN
SEE OTHER CAUTIONS ON BACK PANEL



NET CONTENTS: 5 GALLONS

STEEL DECK
STAINLESS STEEL ACRYLIC LACQUER

A high leafing, pure 316 Stainless Steel Flake, combined with a super tough acrylic lacquer. Provides a hard resistant coating that seals surfaces against corrosion, harsh weather, chemical damage and abrasion. A revolutionary, one package ready to use product that requires no measuring or addition of other ingredients. Flows over and coats surfaces smoothly and evenly. Dries to the touch in 30 minutes. Hardens overnight. Cures to optimum hardness after several days.

EXCELLENT ADHESION TO Metal, Wood, Ceramics, Concrete, Hard Plastic
APPLICATIONS Steam Pipes, Radiators, Fire Hydrants, Exhaust Fans, Mufflers, Parking Meters, Wire Fences, Boilers, Engines, Water Lines, Grills, Lockers, Heat Exchangers, Ovens, Tanks, Chemical Processing and Production Equipment.

DIRECTIONS

AGITATE BEFORE AND DURING USE. DO NOT THIN!

1. Clean surfaces thoroughly prior to application. Remove grease and oil with degreasing solvent. Remove all paint with paint remover then clean surface with degreasing solvent. Remove all loose rust with a wire brush or by sandblasting heavily corroded areas.
2. Creamy suspension lends itself to brush coating sprayers. Dries to the touch in 30 minutes. For maximum toughness and resistance allow surface to dry for several days.
3. Keep container closed when not in use to prevent evaporation and hardening.

RECYCLING

Do not puncture or incinerate container. Consult local authorities for proper disposal of empty containers.

HANDLING AND STORAGE

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld, on or near container, even when empty.

24 Hour Customer Hotline
SOLD BY: 1-800-325-4869



CONTINENTAL RESEARCH CORPORATION
PO Box 15204, St. Louis, MO 63110-0204
24 Hour Fax: (314) 776-6810
on-line: www.crcorp.com • E-mail: crcorp@crcorp.com

STEEL DECK
STAINLESS STEEL ACRYLIC LACQUER

DANGER

FLAMMABLE LIQUID AND VAPOR. Contains VM&P(64742-89-8), Acetone (67-64-1), Stainless Steel Flake (65997-19-5), Xylene (1330-20-7), and Mineral Spirits (64742-47-8). MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks, and flame. **VAPORS MAY CAUSE FLASH FIRE.** Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's direction for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.
IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.
EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
IF INGESTED: Do not induce vomiting. Seek medical attention immediately.
HMIS RATING: Health, 2; Flammability, 3; Reactivity, 0; Personal Protection, B.

KEEP OUT OF REACH OF CHILDREN
For further information consult Material Safety Data Sheet

24 Hour Customer Hotline
SOLD BY: 1-800-325-4869



CONTINENTAL RESEARCH CORPORATION
PO Box 15204, St. Louis, MO 63110-0204
24 Hour Fax: (314) 776-6810
on-line: www.crcorp.com • E-mail: crcorp@crcorp.com



Continental Research Corporation