

Slick Willy

White Lithium Grease

TECHNICAL DATA SHEET



Keeps things running smoothly.



Slick Willy combines the technology of white lithium grease with the convenience of an aerosol. Easily sprayed to coat and prevent rust and corrosion, Slick Willy becomes a durable, non-staining lubricant that provides superior friction reduction between similar or different materials.

- *USDA class H1*
- *Lubricates & reduces friction*
- *Prevents rust & corrosion*
- *PTFE (Teflon) enriched*
- *Non-chlorinated*

Use In:

- | | |
|------------------------|----------------------------------|
| Food Processing Plants | Textile Mills |
| Bottling Plants | Marinas |
| Dairies | Farming |
| Breweries | Water Departments |
| Canneries | Meat & Poultry Processing Plants |

Use On:

- | | |
|----------|-------------------|
| Latches | Equipment |
| Hinges | Tools |
| Bearings | Buckles |
| Rollers | Shackles |
| Tracks | Winch Gears |
| Bolts | Brake Cables |
| Glides | Distributor Caps |
| Locks | Battery Terminals |
| Antennas | |



**Continental
Research
Corporation**

HASSLE FREE BUSINESS SINCE 1967

© 2010 Continental Research Corporation. [070110]

SLICK WILLY™

WHITE LITHIUM GREASE

This product is white lithium grease in a convenient, easy-to-use aerosol can. It is an exceptional coating for the prevention of rust and corrosion. In addition, this PTFE fortified, durable, nonstaining lubricant provides superior friction reduction between similar or different materials than other competing brands. Will not run, wash off, or freeze and does not gum or cake. Use this product on battery terminals, brake cables, distributor caps, latches, hinges, bolts, locks, antennas, equipment, tools, tracks, glides, bearings, rollers, buckles, shackles, winch gears, and other external moving parts or exposed surfaces. Applications for this product can be found in the packaging industry, automotive field, marine and aircraft maintenance. This next generation product is formulated without chlorinated solvents or ozone depleters.

DIRECTIONS

SHAKE WELL BEFORE USING. ALWAYS HOLD CAN UPSIDE DOWN AND SPRAY FOR TWO SECONDS AFTER EACH USE TO PREVENT SPRAY TIP FROM CLOGGING. Hold can 6-10 inches from surface to be lubricated and spray liberally. For hard-to-reach areas, insert extension tube provided.

IMPORTANT: The carrier solvent in this product may damage some plastics and painted surfaces. Always test in an inconspicuous area if unsure of material compatibility. Protect surrounding areas from overspray when needed.

DANGER

Contains Acetone, Heptane and Hydrotreated Light Petroleum Distillates. Extremely flammable. Use only in a well ventilated area. Do not use near heat, sparks, open flame or other sources of ignition. Do not smoke in use area. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. KEEP OUT OF REACH OF CHILDREN.

CAS NUMBERS: Isobutane/Propane Blend 75-28-5/74-98-6; Acetone 67-64-1; Lithium Grease 7620-77-1; Heptane 142-82-5; Hydrotreated Light Petroleum Distillates 64742-47-8

(Equivalent to 15.1 Fluid Ounces)

SOLD BY 24 Hour Customer Hotline
1-800-325-4869
CONTINENTAL RESEARCH CORPORATION
 P.O. Box 15204, St. Louis, MO 63110-0204
 24 Hour Fax: (314) 776-6810
 on-line: www.crcorp.com • E-mail: crcorp@crcorp.com



LUBRICATES & REDUCES FRICTION

FORTIFIED WITH PTFE

PREVENTS RUST & CORROSION

NONCHLORINATED

NO OZONE DEPLETERS

DANGER:

**EXTREMELY FLAMMABLE.
 HARMFUL OR FATAL IF SWALLOWED.
 CONTENTS UNDER PRESSURE.
 KEEP OUT OF REACH OF CHILDREN.
 See back panel for additional precautions.**



NET WT. 11 OZ. (312 GRAMS)



Continental Research Corporation