

Tank Saver

Rust & Corrosion Inhibitor for Metal Water-Storage Tanks



TECHNICAL DATA SHEET



Silicate protect against rust and corrosion in metal water-storage tanks.



This liquid forms a thin, protective film on exposed metal surfaces to inhibit the development of rust and corrosion. Its non-toxic and odorless formula protects all metals, including iron, steel, galvanized steel, brass, bronze, copper and alloys. It does not contain chromates or heavy metals, and it won't leave behind residue.

- *Designed for utility, industrial and municipal storage tanks in fire departments, laundry and hotel water storage systems.*
- *Non-toxic, odorless and tasteless formula.*
- *May be used for potable water without rinsing.*
- *Effective against rust and corrosion.*

Use in metal water-storage tanks:

Fire Departments
Utilities
Laundry/Hotel Water Storage Systems
Emergency Water Supplies
Industrial/Municipal Storage Tanks
Potable Water Tanks



**CONTINENTAL
RESEARCH
CORPORATION**

HASSLE FREE BUSINESS SINCE 1967

© 2010 Continental Research Corporation. [121410]



Tank Saver inhibits rust and corrosion formation in all metal water tanks. Designed for fire departments, utility, industrial and municipal storage tanks, laundry and hotel water storage systems and emergency water supply facilities. It forms a thin protective film on exposed metal surfaces.

This non-toxic, odorless and tasteless inhibitor protects all metals including iron, steel, galvanized, brass, bronze, copper and alloys. It leaves no toxic residue, so treated water tanks may be used for potable water without cleaning or rinsing.

DIRECTIONS

In fire truck tanks, emergency storage tanks, back pack sprayers and holding tanks, add 1 gallon of tank saver for each 1000 gallons of water. Treat every time the tank is filled.

For potable water system: Inject or meter in 10-1/2 to 13 gallons of product with 100,000 gallons of water. Days after the initial treatment, a flush of the system may be required to remove old corrosive deposits that have been cleaned from the metal surfaces.

After a 6-8 week initial treatment period, decrease the feed rate to 5-1/4 to 6-3/4 gallons of product with 100,000 gallons of water.

CAUTION

Irritant. Avoid contact with eyes or prolonged contact with skin. Concentrate may be harmful if swallowed.

FIRST AID

External: Flush with plenty of cool water. **Internal:** Do not induce vomiting. Give person several glasses of water and obtain immediate medical attention. **Eyes:** Flush eye and under eyelids with plenty of cool water for at least 15 minutes and obtain medical attention.

KEEP OUT OF REACH OF CHILDREN

This product contains	CAS Number
Water.....	7732-18-6
Sodium Silicate.....	1344-09-8
627.020606	

NFPA® RATINGS

Flammability 0, Health 0, Reactivity 0



SOLD BY:

Continental Research Corp.
 P.O. Box 15204, St. Louis, MO 63110
 1-800-325-4869 / www.crcorp.com



**CONTINENTAL
 RESEARCH
 CORPORATION**

HASSLE FREE BUSINESS SINCE 1967