

PERMA-SEAL



Perma-Seal self fusing silicone tapes.

Perma-Seal self-adhering silicone tape has no adhesive, leaves no sticky residue, fuses to itself immediately and cures in 24 hours for a permanent seal. Curing time may be shortened by applying heat after wrapping.

- Optimal for high temperature applications, such as electrical coil insulation, splices, cable harnesses and masking applications
- Also useful as an economical substitute for heat shrinkable tubing and hot air ducting
- Perfect for electrical, industrial, automotive, marine and general purpose industries
- Has a tensile strength of 700 PSI and a dielectric strength of 400 volts per wrap for the 20 mil thickness
- Elongation is 300%
- Operating temperature range is -85° to 500°F
- Meets MIL-I-46852C Type I and Type II Standards
- 20 ft. per roll
- Available in case of 6



DCT DURABLE COMPONENT TECH

1-800-285-7965

P.O. BOX 15204, ST. LOUIS, MO 63110

PERMA-SEAL

ORDERING INFORMATION

ALL OF THESE TAPES ARE EXCELLENT FOR ANY APPLICATIONS. BELOW ARE SUGGESTED USES:

WHITE Plumbing. Use to seal hoses, pipes and pvc.

CLEAR Use when seeing the underlying material is necessary

GLOW IN THE DARK For use in low light areas of warehouses, factories, stairwells, basements, and more.

GRAY Gray. Use to bind, choke and seal.

YELLOW Marine use. Highly visible and excellent for sealing ruptured hoses and more.

GREEN Variety of applications. From mending garden hoses to fixing tool handles.

BLUE Variety of applications. Use for grips on tools, ropes and more.

ORANGE Use orange to highlight warning areas and in general purpose applications.

RED Use red to close the positive ends of electrical line.

BLACK Use black to close the negative ends of electrical line.



*The tapes above are printed as accurately as possible and may differ from actual tapes.