

GRAB'N GO PULLERS



Spring loaded for one-person operation.

Parabolic Curved Anvil Head

- Withstands hammer blows and is designed to reduce mushrooming
- Can be turned with standard hex wrench or socket
- Pressure screws feature rolled threads instead of cut threads for greater strength and durability

Yoke

- Forged and heat-treated for maximum strength and durability
- Compatible with slid hammer or pressure screw
- Spring plates allow easy insertion and removal of jaws
- Yoke changes from 2- to 3-jaw

Replaceable Centering Point

- Directs power to prevent cocking of the puller
- Allows easy, friction-free turning of the pressure screw
- Allows replacement of only the centering point, not the whole screw

Forged Jaws

- Inline forging process makes these the strongest and safest jaws available
- Curved design for secure grip
- Reversible; converts from external to internal puller
- Yoke can change from 2- to 3-jaw

Available in 2 to 7-1/2 ton capacity.



Made in U.S.A.

DCT DURABLE COMPONENT TECH

1-800-285-7965

P.O. BOX 15204, ST. LOUIS, MO 63110

GRAB'N GO PULLERS

ORDERING INFORMATION

2 Ton Capacity

SKU #12604

Jaw Length	Number of Jaws	Capacity (Tons)	Maximum Reach	Inside Spread	Outside Spread
Short	2	2	2-1/2"	7/8"-3-1/4"	3"
Long	2	2	3-1/2"	7/8"-3-3/4"	4"

Pressure screw size: 3/8" -16 x 6-1/8"

2-1/2 Ton Capacity

SKU #12415

Jaw Length	Number of Jaws	Capacity (Tons)	Maximum Reach	Inside Spread	Outside Spread
Short	3	2-1/2	2-1/2"	7/8"-3-1/4"	3"
Long	3	2-1/2	3-1/2"	7/8"-3-3/4"	4"

Pressure screw size: 3/8" -16 x 6-1/8"

4-1/2 & 6 Ton Capacity

SKU #12187

Jaw Length	Number of Jaws	Capacity (Tons)	Maximum Reach	Inside Spread	Outside Spread
Short	2	6	3"	1-1/2"-3-1/2"	4-1/2"
Long	2	4-1/2	6"	3/4"-8"	4"

Pressure screw size: 5/8" -18 x 6-7/8"

6 & 7-1/2 Ton Capacity

SKU #12188

Jaw Length	Number of Jaws	Capacity (Tons)	Maximum Reach	Inside Spread	Outside Spread
Short	3	7-1/2	3"	1-1/2"-3"	4-1/2"
Long	3	6	6"	3/4"-8"	4"

Pressure screw size: 5/8" -18 x 6-7/8"