

INDUSTRIAL TAPE



Super strength, multi-purpose tape for quick repair needs.

Features & Benefits

- Excellent adhesion, tack & tensile strength
- Conforms to any surface & will not twist or curl during application
- Durable & long-lasting
- Tears clean
- Polyethylene coated cloth backing
- Available in two strengths: 10 mils Universal & 12 mils Military
- 2 inch x 60 yards per roll

Applications

- Adheres to steel, wood, vinyl, plastic, fabrics & more
- Makes quick repairs to carpets, seats, pipes, cords, wires & more
- Seals ductwork
- Holds insulation materials in place
- Serves as a condensation barrier in refrigeration assemblies

Universal Industrial Tape

- 10 mils
- Available in nine colors: black, blue, brown, burgundy, green, red, silver, white & yellow
- Tested in accordance with UL723 application temperature

Military Industrial Tape

- 12 mils
- Available in military green only
- Meets Federal Specification ASTM D-5486 Type IV, Class I (supercedes PPP-T-60E & PPP-T-60D)

 **DURABLE COMPONENT TECH**

1-800-285-7965

P.O. BOX 15204, ST. LOUIS, MO 63110

INDUSTRIAL TAPE

ORDERING INFORMATION

UNIVERSAL INDUSTRIAL TAPE

Test	Typical Value	Typical Value (Metric)	Test Method
Thickness	10 mils	0.25 mm	ATSM D-1000
Tensile Strength	25.0 lb./in.	0.44 kg/mm	ATSM D-1000
Adhesion to Steel	60 oz./in.	67.2 g/mm	PSTC-1
Adhesion to Backing	34 oz./in.	38.1 g/mm	PSTC-1
Tack (Rolling Ball)	1.25 in.	3 cm	PSTC-1
Max. Performance Temp.	200°F	93°C	

MILITARY INDUSTRIAL TAPE

Test	Typical Value	Typical Value (Metric)	Test Method
Thickness	12 mils	0.304 mm	ATSM D-1000
Tensile Strength	50.0 lb./in.	0.90 kg/mm	ATSM D-1000
Adhesion to Steel	80 oz./in.	89.6 g/mm	PSTC-1
Adhesion to Backing	30 oz./in.	33.6 g/mm	PSTC-1
Max. Performance Temp.	200°F	93°C	

SKU	Color
08818	Black
08814	Blue
08815	Brown
08839	Burgundy
08817	Green
08811	Red
08813	Silver
08812	White
08810	Yellow
08816	Military Green